



cofc

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent No: 7,370,554 B2

Inventor(s): Djordjevic et al.

Serial No. 10/578,288

Examiner: Matthew A. Johnson

Issued: May 13, 2008

Group Art Unit: 3682

Title: **MOVEABLE CONTROL PEDAL ASSEMBLY**

Attorney Docket No: 19339-105590

Mail Stop Certificate of Correction Branch
Commissioner of Patents
PO Box 1450
Alexandria, VA 22313-1450

Certificate
JUN 05 2008
of Correction

REQUEST FOR CERTIFICATE OF CORRECTION

Dear Sir:

Patentees request a Certificate of Correction for U.S. Patent No. 7,370,554. Upon reviewing the issued patent, the patentee noted that the amendments to the specification in the §312 Amendment after Allowance sent on March 13, 2008 and March 19, 2008, respectively, were not properly entered into the issued patent. Therefore, the patentee requests said correction to the specification, which should be corrected as follows:

Please replace paragraph [0016] of the application with the following rewritten paragraph:

-- [0016] Assembly 20 includes a bracket 24 by which assembly 20 is mounted to a vehicle body (not shown) and bracket 24 includes a pair of spaced arms 28a, 28b which extend forwardly from bracket 24. Arms 28a, 28b each include a slot 32a, 32b in which a pedal carriage 36 is carried. As best seen in FIG. 3, pedal carriage 36 comprises carriage sides 40a, 40b to which sliders 44 are mounted. Sliders 44 engage slots 32a, 32b in arms 28a, 28b and allow pedal carriage 36 to move forward and backward along slots 32a, 32b. --

Please replace paragraph [0018] of the application with the following rewritten paragraph:

-- [0018] Each side 40a, 40b of pedal carriage 36 includes a bushing 64a, 64b with a threaded bore 65a, 65b and another bushing 64c with [[the]] a threaded bore 65c is provided on arm 48. The threads of the threaded bore 65a, 65b, 65c in each bushing 64a, 64b, 64c have the same pitch as the threads of the threaded bore 65a, 65b, 65c in each other bushing 64a, 64b, 64c. Bushing 64c on pedal arm 48 is rotatably mounted to pedal arm 48 allowing the threaded bore 65c to remain generally in the same horizontal orientation through the range of movement of pedal arm 48 about pin 52. --

Please replace paragraph [0019] of the application with the following rewritten paragraph:

-- [0019] As best seen in FIGS. 4 and 5, an extender mechanism 68 is mounted to bracket 24 and includes a driver gear 72 and three driven gears 76a, 76b and 76c. Each driven gear 76a, 76b, 76c has a square center passage 77a, 77b, 77c which engages a complementary square cross-sectioned portion 88 of a respective extender rod 80a and 80b and a control rod 84. Each extender rod 80a, 80b, and control rod 84, includes a threaded portion 81a, 81b, 81c which engages the complementary threaded bore 65a, 65b, 65c in [[a]] the respective bushing 64a, 64b, 64c and extender rods 80a and 80b are rotatably mounted to bracket 24 such that lateral movement of extender rods 80a and 80b is prevented while rotation is permitted. --

Please replace paragraph [0020] of the application with the following rewritten paragraph:

-- [0020] Unlike extender rods 80a and 80b, control rod 84 has a longer square cross-sectioned portion 88 which can slide through the square-shaped center passage 77c in driven gear 76c, permitting lateral movement of control rod 84 toward or away from bracket 24 as pedal arm 48 is pressed and released. Further, control rod 84 includes an actuator end 92 which engages a hydraulic cylinder, cable or other control mechanism which pedal arm 48 is intended to operate. --

Please replace paragraph [0021] of the application with the following rewritten paragraph:

-- [0021] As will be apparent, when driver gear 72 is rotated, by, for example, a DC motor 90 via a cable drive [[92]] 94 (shown schematically in FIG. 2) or any other suitable driving means, each driven gear 76a, 76b, 76c turns. As driven gears 76a, 76b, 76c rotate, they each rotate a respective extender rod 80a, 80b and control rod 84 in turn. As extender rods 80a, 80b rotate, each bushing 64a, 64b on carriage sides 40a, 40b move along extender rods 80a, 80b, either moving toward bracket 24 or away from it, depending upon the direction of rotation of driver gear 72. Similarly, as control rod 84 rotates, bushing 64c on pedal arm 48 moves along control rod 84, either moving toward bracket 24 or away from it, depending upon the direction of rotation of driver gear 72. --


Please replace paragraph [0022] of the application with the following rewritten paragraph:

-- [0022] As can now be readily seen, when a suitable driving means is activated by a vehicle operator, rotating driver gear 72, extender rods 80a and 80b and control rod 84 are rotated and bushings 64a, 64b, 64c move along them. As bushings 64a, 64b are moved along extender rods 80a, 80b, pedal carriage 36 moves either toward or away from bracket 24. Pedal arm 48 also moves with pedal carriage 36, toward or away from bracket 24, without altering the lateral positioning of actuator end 92 of control rod 84 and without altering the geometry of pedal arm 48 with respect to pin 52. Thus, the mechanical advantage on control rod 84 provided by pedal arm 48 does not change as pedal carriage 36 is moved along extender rods 80a and 80b. --


Respectfully submitted,

CLARK HILL PLC

Date 6/2/08


Jay S. Paranjpe, Reg. No. 45,486
500 Woodward Avenue, Suite 3500
Detroit, MI 48226-3435
(313) 965-8897
Attorney for Patentees

RECEIVED-USPTO
Patent Publication



TRANSMITTAL LETTER
(General - Patent Issued)

Docket No.
19339-105590

Patentee(s): J. J. Jordjevic et al.

U.S. Patent No.
7,370,554

Issue Date
May 13, 2008

Title:
MOVEABLE CONTROL PEDAL ASSEMBLY

COMMISSIONER FOR PATENTS:

Transmitted herewith is:

PTO-1050, two (2) pp;
Request for Certificate of Correction, 3 pp;
Return Postcard.

- ☐ No additional fee is required.
- ☐ A check in the amount of _____ is attached.
- ☒ The Director is hereby authorized to charge and credit Deposit Account 50-1759 as described below.
- ☒ Charge the amount of \$100.00
- ☒ Credit any overpayment.
- ☒ Charge any additional fee required.
- ☐ Payment by credit card. Form PTO-2038 is attached.

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.


Signature


Dated: 6/2/08

Jay S. Paranjpe, Reg. No. 45,486
Clark Hill PLC
500 Woodward Avenue
Suite 3500
Detroit, MI 48226-3435
(313) 965-8897

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to "Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450" [37 CFR 1.8(a)] on

6/2/2008
(Date)

JUN - 5 2008


Signature of Person Mailing Correspondence

Linda J. Hoggarth

Typed or Printed Name of Person Mailing Correspondence

Customer No.:

cc:

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 7,370,554
 DATED : May 13, 2008
 INVENTOR(S) : Djordjevic et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Please replace paragraph [0016] of the application with the following rewritten paragraph:

— [0016] Assembly 20 includes a bracket 24 by which assembly 20 is mounted to a vehicle body (not shown) and bracket 24 includes a pair of spaced arms 28a, 28b which extend forwardly from bracket 24. Arms 28a, 28b each include a slot 32a, 32b in which a pedal carriage 36 is carried. As best seen in FIG. 3, pedal carriage 36 comprises carriage sides 40a, 40b to which sliders 44 are mounted. Sliders 44 engage slots 32a, 32b in arms 28a, 28b and allow pedal carriage 36 to move forward and backward along slots 32a, 32b. —

Please replace paragraph [0018] of the application with the following rewritten paragraph:

— [0018] Each side 40a, 40b of pedal carriage 36 includes a bushing 64a, 64b with a threaded bore 65a, 65b and another bushing 64c with ~~[[the]]~~ a threaded bore 65c is provided on arm 48. The threads of the threaded bore 65a, 65b, 65c in each bushing 64a, 64b, 64c have the same pitch as the threads of the threaded bore 65a, 65b, 65c in each other bushing 64a, 64b, 64c. Bushing 64c on pedal arm 48 is rotatably mounted to pedal arm 48 allowing the threaded bore 65c to remain generally in the same horizontal orientation through the range of movement of pedal arm 48 about pin 52. —

Please replace paragraph [0019] of the application with the following rewritten paragraph:

— [0019] As best seen in FIGS. 4 and 5, an extender mechanism 68 is mounted to bracket 24 and includes a driver gear 72 and three driven gears 76a, 76b and 76c. Each driven gear 76a, 76b, 76c has a square center passage 77a, 77b, 77c which engages a complementary square cross-sectioned portion 88 of a respective extender rod 80a and 80b and a control rod 84. Each extender rod 80a, 80b, and control rod 84, includes a threaded portion 81a, 81b, 81c which engages the complementary threaded bore 65a, 65b, 65c in ~~[[a]]~~ the respective bushing 64a, 64b, 64c and extender rods 80a and 80b are rotatably mounted to bracket 24 such that lateral movement of extender rods 80a and 80b is prevented while rotation is permitted. —

Please replace paragraph [0020] of the application with the following rewritten paragraph:

— [0020] Unlike extender rods 80a and 80b, control rod 84 has a longer square cross-sectioned portion 88 which can slide through the square-shaped center passage 77c in driven gear 76c, permitting lateral movement of control rod 84 toward or away from bracket 24 as pedal arm 48 is pressed and released. Further, control rod 84 includes an actuator end 92 which engages a hydraulic cylinder, cable or other control mechanism which pedal arm 48 is intended to operate. —

Please replace paragraph [0021] of the application with the following rewritten paragraph:

— [0021] As will be apparent, when driver gear 72 is rotated, by, for example, a DC motor 90 via a cable drive ~~[[92]]~~ 94 (shown schematically in FIG. 2) or any other suitable driving means, each driven gear 76a, 76b, 76c turns. As driven gears 76a, 76b, 76c rotate, they each rotate a respective extender rod 80a, 80b and control rod 84 in turn. As extender rods 80a, 80b rotate, each bushing 64a, 64b on carriage sides 40a, 40b move along extender rods 80a, 80b, either moving toward bracket 24 or away from it, depending upon the direction of rotation of driver gear 72. Similarly, as control rod 84 rotates, bushing 64c on pedal arm 48 moves along control rod 84, either moving toward bracket 24 or away from it, depending upon the direction of rotation of driver gear 72.

MAILING ADDRESS OF SENDER (Please do not use customer number

PATENT NO. 7,370,554 B2

Jay S. Paranjpe, Reg. No. 45,486
 Clark Hill PLC
 500 Woodward Avenue, Suite 3500
 Detroit, MI 48226-3435
 (313) 965-8897

No. of additional copies

 RECEIVED-USPTO
 PAGE 1 of 2 Patent Publication

JUN - 5 2008

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 7,370,554
DATED : May 13, 2008
INVENTOR(S) : Djordjevic et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Please replace paragraph [0022] of the application with the following rewritten paragraph:

-- [0022] As can now be readily seen, when a suitable driving means is activated by a vehicle operator, rotating driver gear 72, extender rods 80a and 80b and control rod 84 are rotated and bushings 64a, 64b, 64c move along them. As bushings 64a, 64b are moved along extender rods 80a, 80b, pedal carriage 36 moves either toward or away from bracket 24. Pedal arm 48 also moves with pedal carriage 36, toward or away from bracket 24, without altering the lateral positioning of actuator end 92 of control rod 84 and without altering the geometry of pedal arm 48 with respect to pin 52. Thus, the mechanical advantage on control rod 84 provided by pedal arm 48 does not change as pedal carriage 36 is moved along extender rods 80a and 80b. --

MAILING ADDRESS OF SENDER (Please do not use customer number

Jay S. Paranjpe, Reg. No. 45,486
Clark Hill PLC
500 Woodward Avenue, Suite 3500
Detroit, MI 48226-3435
(313) 965-8897

PATENT NO. 7,370,554 B2

No. of additional copies

→
PAGE 2 of 2
RECEIVED-USPTO
Patent Registration

JUN - 5 2008